














SPECIFICATIONS

	 ALPINE	 CAMBER	 COCOON	 ENSÖ	 FAUNA	 HAZE	 JEWEL
FABRIC COMPOSITION	100% Solution-Dyed Polyolefin	100% Solution-Dyed Acrylic	100% Polyester	45% Acrylic chenille / 55% Polyester	51% Acrylic / 49% Polyester	100% Solution-Dyed Acrylic	51% Acrylic chenille / 49% Polyester *50% Acrylic chenille / 48.5% Polyester / 1.5% Nylon
WIDTH	135 cms / 53 ins	144 cms / 56.6 ins	150 cms / 59 ins	140 cms / 55 ins	132 cms / 52 ins	140 cms / 55 ins	140 cms / 55 ins
WEIGHT	300 g/m ²	300 g/m ²	300 g/m ²	390 g/m ²	493 g/m ²	300 g/m ²	332 g/m ²
SUITABILITY	GD upholstery & all soft furnishing applications 20,000 Martindale	GD upholstery & all soft furnishing applications 20,000 Martindale	All types of slip covers & towelling accessories	HD upholstery & all soft furnishing applications 30,000 Martindale	SC upholstery & all soft furnishing applications 40,000 Martindale	GC upholstery, drapes & all soft furnishing applications 35,000 Martindale	HD upholstery, drapes & all soft furnishing applications 25,000 Martindale
COLOUR FASTNESS	Saline Durable Chlorine Durable	Saline Durable (BS EN ISO 105 E02: 2013) Chlorine Durable (BS EN ISO 105 E03: 2010)	Chlorine Durable (BS EN ISO 105 E03: 2010)	Saline Durable (BS EN ISO 105 E02: 1996) Chlorine Durable (BS EN ISO 105 E03:1997)	Saline Durable (BS EN ISO 105-E02:1996) Chlorine Durable (BS EN ISO 105-E03:2010)	Saline Durable (BS EN ISO 105 E02: 1996) Chlorine Durable (BS EN ISO 105 E03: 1997)	Saline Durable (BS EN ISO 105 E02: 2013) Chlorine Durable (BS EN ISO 105 E03: 2010)
LIGHT FASTNESS	Fade resistant (Grade ≥ 7 BS EN ISO 105: B02: 2014)	Fade resistant (Grade = 7 BS EN ISO 105: B02: 2013)	Fade resistant (Grade ≥ 6 BS EN ISO 105: B02: 1999)	Fade resistant (Grade ≥ 7/8 BS EN 20105: B02: 1993)	Fade resistant (Grade ≥ 7 BS EN ISO 105: B02: 1999)	Fade resistant (Grade ≥ 7/8 BS EN ISO 105: B02: 1999)	Fade resistant (Grade ≥ 6 BS EN ISO 105: B02: 2013)
STAIN RESIST	Resistant to liquid stains	Soil, stain & water repellent	N/A	Soil, stain & water repellent	Soil, stain & water repellent	Soil, stain & water repellent	Soil, stain & water repellent
CLEANING	Machine washable (max. 30°C) Spongeable	Machine washable (max. 40°C) Spongeable Dry-cleanable Tumble dry (max. 40°C)	Machine washable Tumble dry (max. 40°C recommended)	Machine washable (max. 40°C) Spongeable Dry-cleanable Tumble dry (max. 40°C)	Machine washable (max. 40°C) Spongeable Dry-cleanable Tumble dry (max. 40°C)	Machine washable (max. 40°C) Spongeable Dry-cleanable Tumble dry (max. 40°C)	Machine washable (max. 40°C) Spongeable Dry-cleanable Tumble dry (max. 40°C)
SHRINKAGE	Machine wash (BS EN ISO 6330: 2001)	Machine wash (BS EN ISO 6330: 2001) Dry cleaning (Commercial)	Machine wash (BS EN ISO 6330: 2001)	Machine wash (BS EN ISO 6330: 2001) Dry cleaning (Commercial)	Machine wash (BS EN ISO 6330:2001) Dry cleaning (Commercial)	Machine wash (BS EN ISO 6330: 2001) Dry cleaning (Commercial)	Machine wash (BS EN ISO 6330: 2012) Dry cleaning (Commercial)
FLAME RETARDANCY	N/A	With treatment meets BS 5852 Cigarette.	N/A	Many international flammability codes can be met with appropriate FR treatment.	Some international flammability codes can be met with appropriate FR treatment.	With treatment meets BS 5852 Cigarette & Match. Can also meet IMO 652.	Some international flammability codes can be met with appropriate FR treatment.
WARRANTY	3 years	2 years	N/A	2 years	2 years	3 years	2 years

SPECIFICATIONS

						
	MULL	OUTLINE	PLUME	SOLAR	SPICE	WAVE
FABRIC COMPOSITION	45% Acrylic chenille / 55% Polyester	45% Acrylic chenille / 55% Polyester	45% Acrylic chenille / 55% Polyester	100% Solution-Dyed Acrylic	45% Acrylic chenille / 55% Polyester	100% Solution-Dyed Acrylic
WIDTH	140 cms / 55 ins	140 cms / 55 ins	140 cms / 55 ins	140 cms / 55 ins	140 cms / 55 ins	140 cms / 55 ins
WEIGHT	332 g/m ²	332 g/m ²	332 g/m ²	352 g/m ²	280 g/m ²	440 g/m ²
SUITABILITY	HD upholstery, drapes & all soft furnishing applications 28,000 Martindale	GD upholstery, drapes & all soft furnishing applications 23,000 Martindale	GD upholstery & all soft furnishing applications 20,000 Martindale	LD upholstery & all soft furnishing applications 15,000 Martindale	GD upholstery, drapes & all soft furnishing applications 20,000 Martindale	GD upholstery & all soft furnishing applications 21,000 Martindale
COLOUR FASTNESS	Saline Durable (BS EN ISO 105 E02: 1996) Chlorine Durable (BS EN ISO 105 E03:1997)	Saline Durable (BS EN ISO 105 E02: 1996) Chlorine Durable (BS EN ISO 105 E03:1997)	Saline Durable (BS EN ISO 105 E02: 2013) Chlorine Durable (BS EN ISO 105 E03: 2010)	Saline Durable (BS EN ISO 105 E02: 1996) Chlorine Durable (BS EN ISO 105 E03: 2010)	Saline Durable (BS EN ISO 105 E02: 1996) Chlorine Durable (BS EN ISO 105 E03:1997)	Saline Durable (BS EN ISO 105 E02: 1996) Chlorine Durable (BS EN ISO 105 E03: 1997)
LIGHT FASTNESS	Fade resistant (Grade ≥ 7/8 BS EN 20105: B02: 1993)	Fade resistant (Grade ≥ 7/8 BS EN 20105: B02: 1993)	Fade resistant (Grade ≥ 7 BS EN ISO 105: B02: 2014)	Fade resistant (Grade ≥ 7/8 BS EN ISO 105: B02: 1999)	Fade resistant (Grade ≥ 6 BS EN ISO 105: B02: 1999)	Fade resistant (Grade ≥ 7/8 BS EN ISO 105: B02: 1999)
STAIN RESIST	Soil, stain & water repellent	Soil, stain & water repellent	Soil, stain & water repellent	Soil, stain & water repellent	Soil, stain & water repellent	Soil, stain & water repellent
CLEANING	Machine washable (max. 40°C) Spongeable Dry-cleanable Tumble dry (max. 40°C)	Machine washable (max. 40°C) Spongeable Dry-cleanable Tumble dry (max. 40°C)	Machine washable (max. 40°C) Spongeable Dry-cleanable Tumble dry (max. 40°C)	Machine washable (max. 40°C) Spongeable Dry-cleanable Tumble dry (low temp. setting)	Machine washable (max. 40°C) Spongeable Dry-cleanable Tumble dry (max. 40°C)	Machine washable (max. 40°C) Spongeable Dry-cleanable
SHRINKAGE	Machine wash (BS EN 26330: 1994) Dry cleaning (BS EN 25077: 1994)	Machine wash (BS EN 26330: 1994) Dry cleaning (BS EN 25077: 1994)	Machine wash (BS EN ISO 5077: 2008) Dry cleaning (Commercial)	Machine wash (BS EN ISO 6330: 2001) Dry cleaning (Commercial)	Machine wash (BS EN ISO 6330: 2001) Dry cleaning (BS EN ISO 3175-2: 1998)	Machine wash (BS EN ISO 6330: 2001) Dry cleaning (Commercial)
FLAME RETARDANCY	With treatment meets BS 5852 Cigarette, Match & Crib 5. Can also meet IMO 652.	With treatment meets BS 5852 Cigarette, Match & Crib 5. Can also meet IMO 652.	Some international flammability codes can be met with appropriate FR treatment.	With treatment meets BS 5852 Cigarette.	With treatment meets BS 5852 Cigarette, Match & Crib 5. Can also meet IMO 652.	Meets the requirements of BS 5852 Cigarette.
WARRANTY	2 years	2 years	2 years	2 years	2 years	3 years